VOC

containment systems

Specification Sheet
PMR-20
Paint Mixing Room

PMR Shell:	10'0" Long x 8'0" Wide x 9'2" High (OD) 18 Gauge Galvanized Steel Panels "TUFF WHITE" Powder Coating
Access Door:	(1) Total, 36" Wide x 86" High Double-Paneled Tube Constructed Tempered Safety View Glass Handle Latch, Rubber Edge Seal
Intake Filter:	(2) Total, 20" x 20" x 2 Reinforced Wire Framed Easy Maintenance Rated at 10 Micron High Efficiency
Exhaust Fan:	(1) Total, 12" Diameter Tubeaxial Fan, Heavy Duty Aluminum Non-Sparking Balanced Blade
Exhaust System:	(2) Total, 12" x 5' Duct (1) Total, 12" All-Weather Stack Heads
Fan Motor:	(1) Total, 1 HP, Single PH, TEFC/ODP
Lights:	(2) Total, 48", 4 Tube, 110 Volt, UL Approved Fixture. Enclosed Light Fixtures.
Light Glass:	(2) Total, 3/16" Tempered Safety Glass.
Hardware:	All Necessary Hardware and Trim Packages
Note:	All PMR Construction Meets or Exceeds N.F.P.A. 30 and 33